



## Glancetron K600

Entry-level all-in-one touch POS

- POS system with integrated touch screen
- Highly robust housing (IP54 rating), water and dust resistant
- Reliable quiet fanless operation
- Excellent value for the money
- Optional magnetic card reader, second monitor and customer display

### Specifications

System	CPU	Intel Atom D525 Dual Core, 1.8 GHz (fanless)
	Chip set	Intel ICH8M
	System memory	1GB DDR3 memory (max. 4GB)
	Hard disk drive	1x (2.5") SATA HDD, 160GB
	Audio	onboard
	Housing	ABS
	Supported operating systems	Windows XP Professional, Embedded POSReady 2009, XP Embedded, XP Professional for Embedded, WinCE, Windows 7, Linux
Display	Graphics chip	Intel integrated
	LCD screen size	38.1 cm (15")
	Maximum resolution	1024 x 768 pixels
	Brightness	250 cd/m <sup>2</sup>
	Touch screen	resistive (5-wire)
Interfaces	USB 2.0	4x
	Serial/COM	4x RJ45 (COM1/COM2 standard RS232, COM3 with 5V to Pin 9, COM4 with 12V to Pin 9)
	Parallel	1x
	LAN	1x Gigabit
	VGA	1x
	PS/2	n/a
	Cash drawer port	1 x RJ-11 (12V/24V cash drawer)
	Audio	1x Line-out, 1x Mic-in
PSU	Power adapter	90 watts (19V, 4.7A)
Miscellaneous	Dimensions (WxDxH)	380 x 300 x 221.7 mm
	Weight	6.6 kg
	Operating temperature	5°C to 35°C
	Certifications	FCC, CE, LVD
	Mounting options	stand / VESA (100 x 100 mm)
Options	Magnetic stripe reader	track 1, 2 and 3
	Customer display	VFD, 2x20 characters
	Customer-facing screen	21.3 cm (8.4"), 26.4 cm (10.4") or 30.7 cm (12.1") screen size



Your partner