T5DV

15" TFT-LCD Touch Monitor



Introduction

T Series monitor families are a flat LCD display with the wide-view angle and the most cost-efficient type. The series of monitors are designed and developed for the application of POS display, industrial field, medical and transportation. They provide all the features, such as to support touchscreen (Resistive) and VGA signal. With the friendly OSD and multi-language support, users can freely operate the series of products without struggling. To touch the screen with a finger, fingernail or object such as a credit card and you will receive a fast, accurate response every time.

Specification:

I/O Ports VGA Input: 15 Pins D-Sub x1
Plug & Play VESA DDC1/2B Compatible Support

OSD Control

Keys: Auto-tune, menu, decrease and increase
Functions: Brightness, Contrast, Clock, Phase,

Horzontal Position, Vertical Position

Power Consumption 24W max.

Power Build-in power supply, with AC 100~240V Tilt Angle -25°~90° or -4°~90° for desk-top without

additional parts

Dimensions(WxHxD) 357 mm x 344 mm x 210 mm

Net Weight 5.2 kg±1

Environment

Operating Temperature -0~45°C

Storage Temperature
 Humidity
 EMC Approved
 Safety Approved
 UL/ Cus

Display

· LCD Diagonal Size(inch) 15"

• **Resolution** XGA (1024 x 768)

Mode TN
 Response Time(ms) 16
 Number of Colors 16.2M

• View Angle(H/V) H:140° / V:130°

Brightness(cd/m²)(Typ.) 250 nits
Contrast Ratio(ms)(Typ.) 450:1
Lamp Lift(hours) 50,000

Touchscreen

Туре	5-Wire Resistive
Thickness	3mm
Resolution	Continuous
Light Transmission	≧80%
Controller Interface	RS-232 or USB
Power Consumption	+5V@200mA
Touch Lifetime (Finger)	35 Million Times
Driver OS Support	DOS, Linux and Windows® 95 / 98 / NT / ME / 2000 / XP

- * 15" TFT Panel 250 nits testing for reference.
- * RS-232 Interface by NCT option.
- * All Touch specifications are subject to be changed without notice.

