

Epson TM-P60II Series

DATASHEET



The Epson TM-P60II is a second-generation, wireless mobile receipt printer from the world's leading POS printer manufacturer ¹. Offering a brilliantly simple printing solution, the hand-held TM-P60II prints directly from mobile devices² – no drivers needed.

Unique, built-in intelligence, called Epson ePOS-Print, enables the TM-P60II to receive XML commands from web applications, and to print directly from popular web browsers. This makes integration and maintenance easy.

To help serve customers quickly, the high-performance TM-P60II prints receipts at up to 100mm/sec. Drop-in paper loading ensures there are no delays.

The TM-P60II is designed for maximum reliability, with a rugged case. Its battery lasts for up to 46 hours in Bluetooth mode, and up to four batteries can be charged simultaneously using the optional charging unit.

KEY FEATURES

- Wireless, hand-held POS printing
- Prints receipts at up to 100mm/sec
- Compact and robust design
- XML command compatible
- No drivers to install or update

PRODUCT SPECIFICATIONS

Print method	Thermal line printing
Print speed	100 mm/sec
FONTS & STYLES	
Column capacity	Paper width 60 mm
PAPER	
Paper size	58,00 ± 60,00 (W) mm x dia 51,00 mm
FONTS & STYLES	
Print Speed	100 mm/sec
Print Speed receipt	100 mm/sec
Printing Font	ANK
Column capacity receipt	Paper width 60 mm
Dot density	203 dpi x 203 dpi
Color Printing	Black
INTERFACES	
Interfaces	USB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)
DATA BUFFER	
Data Buffer	0 kB or 4.096 Bytes
POWER	
Power Supply	PS-11
Battery Life	WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours
Operating voltage	24 V
GENERAL	
Product dimensions	103 x 159 x 65 (Width x Depth x Height)
Product weight	0,63 kg
Color	Black (EBCK)
Noise Level	Operation: 53 dB (A)
Humidity	Operation 10% - 90%
STANDARDS COMPLIANCE	
EMC Standards	FCC class A, CE marking
Safety standards	UL, CSA, EN
OTHER FEATURES	
Cutter	Partial Cut
OTHER	
Warranty	12 months Carry in

LOGISTICS INFORMATION

Dimensions Single Carton	229 x 185 x 104 mm
Carton Weight	1 Kg
Multiple Order Quantity	1 Units
Pallet Size Euro	432 Units (54 x 8)



*Source: Interconnection Consulting 2012



Better Products
for a Better Future

<http://eco.epson.com>

Epson Deutschland GmbH
Otto-Hahn-Str. 4
D-40670 Meerbusch
Info-Line: 01805/23 41 10 (0,14 /Min. aus dem dt. Festnetz,
max. 0,42 /Min. aus dem Mobilfunk)
Telefax: +49 (0) 2159/538-3000
www.epson.de

Epson in Österreich
Info-Line: 0810/20 01 13 (0,07 /Min.)
www.epson.at
Epson in der Schweiz
Info-Line: 0848 44 88 20 (8 Rp./Min.)
www.epson.ch

Alle Marken und eingetragenen Warenzeichen sind das Eigentum der Seiko Epson Corporation oder der jeweiligen Rechteinhaber.
Diese Produktinformationen können ohne vorherige Ankündigung geändert werden.

Epson TM-P60II Series

WHAT'S IN THE BOX

- Battery (OY-BY60II)
- Belt clip
- Cable fixation saddle
- Main unit
- Roll paper
- USB cable

SUPPLIES

- 3yr CoverPlus Pack 30 RTD
- OT-CH60II (374): Multi battery charger for TM-P60II C32C825374
- PS-11 (375): Power supply for TM-P60II C32C825375
- OT-BY60II (091): Lithium-ion battery for TM-P60II C32C831091
- 3yrs on-site swap

OPTIONAL ACCESSORIES

- OT-CH60II (374): Multi battery charger for TM-P60II C32C825374
- PS-11 (375): Power supply for TM-P60II C32C825375
- OT-BY60II (091): Lithium-ion battery for TM-P60II C32C831091

1. Source: Futuresource Consulting Limited,
www.futuresource-consulting.com

2. ePOS-Print is available in WLAN mode only

Epson TM-P60II Peeler Series

DATASHEET



The Epson TM-P60II Peeler is a second-generation, wireless mobile label printer from the world's leading POS printer manufacturer¹. Offering a brilliantly simple printing solution, the hand-held TM-P60II Peeler prints directly from mobile devices² – no drivers needed.

Unique, built-in intelligence, called Epson ePOS-Print, enables the TM-P60II Peeler to receive XML commands from web applications, and to print directly from popular web browsers. This makes integration and maintenance easy.

Ideal for shelf-edge labelling and product tagging, the TM-P60II Peeler gets the job done quickly with high-performance printing at up to 80mm/sec. Drop-in paper loading helps save time.

The TM-P60II Peeler is designed for maximum reliability, with a rugged case. Its battery lasts for up to 46 hours in Bluetooth mode, and up to four batteries can be charged simultaneously using the optional charging unit.

KEY FEATURES

- Wireless, hand-held label printing
- Prints labels at up to 80mm/sec
- Compact and robust design
- XML command compatible
- No drivers to install or update

PRODUCT SPECIFICATIONS

Print method	Thermal line printing
Print speed	100 mm/sec
FONTS & STYLES	
Column capacity	Paper width 60 mm
PAPER	
Paper size	58.00 ± 60.00 (W) mm x dia 51.00 mm
FONTS & STYLES	
Print Speed (label)	80 mm/sec
Print Speed (peeler mode)	40 mm/sec
Print Speed receipt	100 mm/sec
Printing Font	ANK
Column capacity receipt	Paper width 60 mm
Dot density	203 dpi x 203 dpi
Color Printing	Black
INTERFACES	
Interfaces	USB 2.0 Type Mini-B, Wireless LAN IEEE 802.11b/g/n (optional), Bluetooth (optional)
DATA BUFFER	
Data Buffer	0 kB or 4,096 Bytes
POWER	
Power Supply	PS-11
Battery Life	WiFi 14 Hours, WiFi (Energy saving mode) 27 Hours, Bluetooth 46 Hours
Operating voltage	24 V
GENERAL	
Product dimensions	103 x 159 x 65 (Width x Depth x Height)
Product weight	0.61 kg
Color	Black (EBCK)
Noise Level	Operation: 53 dB (A)
Humidity	Operation 10% - 90%
STANDARDS COMPLIANCE	
EMC Standards	FCC class B, CE marking
Safety standards	UL, CSA, EN
OTHER	
Warranty	12 months Carry in

LOGISTICS INFORMATION

Dimensions Single Carton	229 x 185 x 104 mm
Carton Weight	1 Kg
Multiple Order Quantity	1 Units
Pallet Size Euro	432 Units (54 x 8)

Epson TM-P60II Peeler Series

WHAT'S IN THE BOX

- Battery (OY-BY60II)
- Belt clip
- Cable fixation saddle
- Main unit
- Roll paper
- USB cable

SUPPLIES

- 3yr CoverPlus Pack 30 RTD
SESHQ2200
- 3yrs on-site swap
- PS-11 (375): Power supply for TM-P60II
C32C825375
- OT-CH60II (374): Multi battery charger for TM-P60II
C32C825374
- OT-BY60II (091): Lithium-ion battery for TM-P60II
C32C831091

OPTIONAL ACCESSORIES

- PS-11 (375): Power supply for TM-P60II
C32C825375
- OT-CH60II (374): Multi battery charger for TM-P60II
C32C825374
- OT-BY60II (091): Lithium-ion battery for TM-P60II
C32C831091

For more information please contact:

Telephone: 0871 222 6702 (UK)+
01 436 7742 (Republic of Ireland)

E-mail: enquiries@epson.co.uk
Chat: etalk.epson-europe.com
Fax: 0871 222 6740

Web: www.epson.co.uk
www.epson.ie

+ Calls cost 10p per minute plus network extras.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.

1. Source: Futuresource Consulting Limited,
www.futuresource-consulting.com

2. ePOS-Print is available in WLAN mode only

EPSON[®]