

P2V



- Professional card printer for ID cards, name tags, customer cards and much more
- Creates plastic cards in various thicknesses, full colour in high quality (12 dots/mm, 300 dpi)
- Prints single-sided at high speed
- Single or automatic feeding for up to 100 cards
- Includes card printing software with high functionality (full version)
- Optionally with magnetic or smart card as well as RFID encoder

Specifications

Print

Technology	Dye sublimation (colour), thermal transfer (monochrome)
Printing speed	Multicoloured: 26 sec.
Printing pages	Single sided (option: double-sided)
Resolution	12 dots/mm (300 dpi)
Pulse life	1 x 108 pulses, print head abrasion: 50 km
Colour	Full colour (16.7 million colours)
Feeder	Single feeder, multi-feeder (min. 100 pcs), output tray (min. 70 pcs)
Ink Ribbon	200 cards/roll (YMCKO)

Electronics

CPU	32 bit processor
RAM	16 MB
User interface	LCD, LED, switch
Power supply	Input: AC 100 ~ 240 V / 50 ~ 60 Hz, Output: 24 V DC
Fonts	True Type fonts via Windows Driver

Cards

Quality and dimensions (WxL)	PVC - ISO CR-80-ISO 7810; (53.98 x 85.7 x 0.2 ~ 1.2 mm)
------------------------------	---

Encoding (optional)

Magnetic stripe	ISO7811 (track 1,2,3), HiCo/LoCo
Contact (IC)	ISO7816, EMV, K-cash
Contactless (RF)	ISO14443 A,B, ISO 15693, MiFare
Bar codes	Code 39, Code 128 B & C, UPC-A, EAN 8 & 13, PDF-417 2D

Interfaces

I/F ports	USB 2.0, RS232C, (Option: Ethernet (TCP/IP) 10/100 Mbps)
-----------	--

Software

System requirements	Windows 2000, XP /Vista (32bit)
---------------------	---------------------------------

Environment

Operating temperature	5°C ~ 45°C
Storage temperature	-25°C ~ 70°C
Humidity	20 ~ 70% RH (non-condensing)

Dimensions /Weight

LxHxW	403 x 192 x 202 mm / 5.5 kg
-------	-----------------------------

Warranty

Period	24 months
--------	-----------



Subject to change without notice.

Your Dealer

www.point2vente.com