

P2V L-1 – Favourably priced Label Printer

WWW.

Highlights

- Professional direct thermal label printer in a complete package
- Maximum label width: 112mm, maximum speed: 127mm/sec.
- PSU and 3-fold interface (serial, parallel and USB onboard) included
- Ethernet and/or version with auto-cutter optional
- Integrated dispenser as standard

Technical specifications

Print

Printing method	Direct thermal
Print width	25.4mm ~ 104 mm
Print speed	127 mm/sec.
Resolution	8dots/mm (203dpi)
Consumables	Thermal paper labels
Paper roll diameter	130mm (outer); 25.4 mm ~ 38.1 mm (inner)
Bar codes	Code 39, Code 128, interleave 2 of 5, Coda Bar, UPC-A, UPC-E, EAN-8, EAN-13, UCC-EAN128, Maxicode (2D), QR Code (2D), PDF 417 (2D)

Electronics

Emulation	SLCS, EPL II, ZPL II, ESC/POS
Sensors	Gap, Black Mark, Notch Sensor, Continuous Fan-Fold
Power supply	Input: AC 100V ~ 240V ± 10 % (included); output: DC 24V, 3.75A
Character set	Alphanumeric: 95 character; extended character page: 128 x 22; international: 32 character; bitmap fonts: 10 character
Reliability	MCBF: min. 12 months; auto-cutter: min. 6 months; TPH: min. 6 months

Specifics

Options	Auto-cutter, wall mount bracket, Ethernet
---------	---

Interfaces

I/F ports	RS232, parallel, USB (all standards)
-----------	--------------------------------------

Software

Drivers	Windows 2000, XP (32/64 Bit), 2003 Server (32/64 Bit), Vista (32/64 Bit), Windows 7 (32/64 Bit), OPOS
---------	--

Housing

Dimensions (WxHxD)	184 x 171 x 221 mm
Colour	White

Warranty

Period	24 months
--------	-----------



1
METAPACE