

P2V-15 ^{WIDE}

Professional Wide Touch Screen



- High-end 38.1 cm (15") LCD monitor for most demanding applications
- Integrated touch screen using 5-wire resistive touch technology
- Highly elegant design featuring an extremely robust construction
- Dual touch screen interface: RS232/USB with dual power input
- Maximum resolution: 1366x768 pixels

Specifications

Display	LCD size / type	38.1 cm (15") TFT active matrix panel
	Touch technology	5-wire resistive
	Touch interface	RS232 (DB-9) / USB (type B)
	Visible surface	344.2 x 193.5 mm (H x V)
	Pixel pitch	0.252 x 0.252 mm (H x V)
	Resolution	1366 x 768 pixel
	Display mode	VGA 720 x 400 (70 Hz), VGA 640 x 480 (60/66/70/72/75 Hz), SVGA 800 x 600 (60/70/72/75 Hz), SVGA 832 x 624 (74.55 Hz), XGA 1024 x 768 (60/70/75 Hz), WXGA 1280 x 768 (60 Hz), WXGA 1366 x 768 (60 Hz)
	Display colours	16.7 millions
	Contrast	500 : 1
	Brightness (resistive)	212 cd/m ² (typical)
	Response time	Tr + Tf: 8 ms
	Viewing angle	Horizontal: 90° / Vertikal: 65°
	General	Video input format
Video input frequency		Horizontal: 31.47 kHz ~ 60.02 kHz / vertical: 56 Hz ~ 75 Hz
Video signal input		15-pin D-sub (female, analogue)
Colour		Black
Dimensions		388 x 272 x 214 mm (W x H x D)
Weight / Shipping weight		4.8 kg / 7.1 kg
Power supply unit		DC 12 V / 4.16 A
Power consumption		Operation: 20 W / standby: 4 W / off: 2 W
Mounting options		Stand / 100 x 100 mm VESA wall mount
Function keys		Power on/off, Select, Up, Down, Menu
Audio		1 W speakers / 2 channels
Temperature - operation / storage	0°C ~ 40°C / -20°C ~ 60°C	
Humidity - operation / storage	20% ~ 80% / 10% ~ 90% (non-condensing)	



Your Dealer

P2V-19 ^{WIDE}

Professional Wide Touch Screen



- High-end 47 cm (18.5") LCD monitor for most demanding applications
- Integrated touch screen using 5-wire resistive touch technology
- Highly elegant design featuring an extremely robust construction
- Dual touch screen interface: RS232/USB with dual power input
- Maximum resolution: 1366x768 pixels

Specifications

Display	LCD size / type	47 cm (18.5") TFT active matrix panel
	Touch technology	5-wire resistive
	Touch interface	RS232 (DB-9) / USB (type B)
	Visible surface	409.8 x 230.4 mm (H x V)
	Pixel pitch	0.3 x 0.3 mm (H x V)
	Resolution	1366 x 768 pixel
	Display mode	VGA 720 x 400 (70 Hz), VGA 640 x 480 (60/66/70/72/75 Hz), SVGA 800 x 600 (60/70/72/75 Hz), SVGA 832 x 624 (74.55 Hz), XGA 1024 x 768 (60/70/75 Hz), WXGA 1280 x 768 (60 Hz), WXGA 1366 x 768 (60 Hz)
	Display colours	16.7 millions
	Contrast	1000 : 1
	Brightness (resistive)	200 cd/m ² (typical)
	Response time	Tr + Tf: 5 ms
	Viewing angle	Horizontal: 170° / vertical: 160°
	General	Video input format
Video input frequency		Horizontal: 31.47 kHz ~ 60.02 kHz / vertical: 56 Hz ~ 75 Hz
Video signal input		15-pin D-sub (female, analogue)
Colour		Black
Dimensions		458 x 312 x 214 mm (W x H x D)
Weight / Shipping weight		5.7 kg / 8.1 kg
Power supply unit		DC 12 V / 4.16 A
Power consumption		Operation: 25 W / standby: 3 W / off: 1 W
Mounting options		Stand / 100 x 100 mm VESA wall mount
Function keys		Power on/off, Select, Up, Down, Menu
Audio		1 W speakers / 2 channels
Temperature - operation / storage	0°C ~ 40°C / -20°C ~ 60°C	
Humidity - operation / storage	20% ~ 80% / 10% ~ 90% (non-condensing)	



Your Dealer